

Wellsaw®
MADE IN U. S. A.

MODEL 1118SA

Semi-Automatic Bandsaw



**WELLSAWS work harder and last longer
because they are built better.**

Wellsaw®
MADE IN U. S. A.

2829 N. Burdick St.
Kalamazoo MI 49004
Phone: 269-345-1132
Fax: 269-345-0095
www.wellsaw.com



Model 1118SA

Semi-Automatic Bandsaw

Manufactured in the United States of America

The **Wellsaw Model 1118SA** gives you the strength and precision of our popular manual saw with the convenience of a semi-automatic. The factory programed PLC controls the saw head and bed vise for improved safety and increased productivity.

Standard Features Include:

- CTrue PLC Semi-Automatic Operation
- CVariable Hydraulic Feed Rate
 - with Positive Dowfeed Control
- CCombination Spring loaded Carbide Guides
 - with Rollers
- C Perimeter Ring Gear Blade Drive
- CBaldor® Motor
- CInfinitely Variable Blade Speeds
- CRite-Tension® Band Tensioning Device
- CPrecision Ground Bed
- CWet Cutting System
- CPowered Blade Brush
- C110 Volts at Controls
- CMagnetic Starter with Overload
 - and Undervoltage Protection
- CQuick Acting Vise / Air Powered
- CAdjustable Stock Stop
- CAuto Shut-Off at End of Cut
- COSHA Blade Guarding
- CTiger-Tooth Bi-Metal Blade
- CCoolant for Initial Start-Up

Options Available:

- CChip Conveyor
- CBlade Break/Stall Switch
- CFused Disconnect
- CWorking Light w/ transformer
- C5' and 10' Non-Powered Conveyors

Specification subject to change without notice.

The Original....Since 1926

Wellsaw
MADE IN U. S. A.



2829 N Burdick St.
Kalamazoo MI 49004
Phone: 269-345-1132
Fax: 269-345-0095
www.wellsaw.com

Specifications:

Capacity	
Round	13"
Flat	18"
Rectangular	13" x 18"
45E Angle	11-1/2" x 9 -1/2"
Blade Size	1" x .035 x 12'6"
Blade Speeds	70-375 SFPM Infinitely Variable
Blade Guides	Carbide Guides with Rollers
Blade Tension	Manual Rite-Tension®
Electrical Options	2 HP Single Phase ODP 115-208-230/60/1
	3 HP / 3 Phase TEFC 208-230-460/60/3
Coolant System	
Tank Capacity	8 gallons
Submersible Pump	115Volt/ .6 Amp/ 170 GPH
Vise Control	Manual Screw
Swivel Vise	To 45E
System Logic	PLC / Non-Volatile Memory
Air Requirement	5CFM @ 90PSI
Bed Height	35"
Floor Area	40"W x 84"L
Shipping Weights 1200 Lbs.	